



# HSM SECURIO B35 - 1 x 5 mm




## HSM SECURIO B35 document shredder

For more data security in the workplace. The excellent document shredder with an intake width of 400 mm for professional data destruction in an open-plan office for up to eight people.

### Technical data

<b>Order number:</b>	1924111	<b>Voltage / Frequency:</b>	230 V / 50 Hz
<b>EAN</b>	4026631044257	<b>Intake width:</b>	400 mm
<b>Cutting type:</b>	particle cut	<b>Container volume / collecting:</b>	130 l
<b>Cutting width:</b>	1 mm	<b>Noise level (idle operation):</b>	ca. 56 dB(A)
<b>Particle length:</b>	5 mm	<b>Weight x Depth x Height:</b>	620 x 525 x 870 mm
<b>Security level (DIN 66399):</b>	F-3   P-7	<b>Weight:</b>	53,7 kg
<b>Cutting capacity in sheets 80g/m<sup>2</sup>:</b>	5	<b>Shredder material:</b>	Paper
<b>Power consumption:</b>	590 W		

### Product information



The induction-hardened, solid steel cutting rollers guarantee durability.



Reusable cardboard box as bin for shredded material.



The full bin is indicated via the display and the machine switches off automatically.

# HSM®



### For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



### Energy-saving

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



### High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



### Automatic start/stop

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.



### Anti-paper jam function

The paper feed with overload protection reduces paper jams and sustains the high throughput of paper.



### Convenient emptying

Robust wooden cabinet with castors. After opening the door, the reusable collecting bag can be easily removed and emptied.



[www.huer-engel.de/uz174](http://www.huer-engel.de/uz174)

Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).

