



HSM SECURIO B32 - 1.9 x 15 mm + external autom. oiler



HSM SECURIO B32 document shredder

High quality materials, proven quality – the reliable security partner in the workplace. With an intake width of 310 mm, the document shredder effortlessly shreds DIN A3 paper. It is the perfect device for working groups.


Technical data

Order number:	18221110	Voltage / Frequency:	230 V / 50 Hz
EAN	4026631031363	Intake width:	310 mm
Cutting type:	particle cut	Container volume / collecting:	82 l
Cutting width:	1,9 mm	Noise level (idle operation):	ca. 56 dB(A)
Particle length:	15 mm	Weight x Depth x Height:	497 x 398 x 793 mm
Security level (DIN 66399):	E-4 F-2 P-5 T-5	Weight:	30 kg
Cutting capacity in sheets 80g/m²:	9 - 11	Shredder material:	Paper, Staples and paper clips, Credit card
Power consumption:	500 W		

Product information



For a consistently high cutting performance, this low maintenance document shredder has an external automatic oiler as an option.



The induction-hardened, solid steel cutting rollers guarantee durability.



The full bin is indicated via the display and the machine switches off automatically.





For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



Energy-saving

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



Automatic start/stop

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.



Display bin full

The full bin is indicated via the display and the machine switches off automatically.



Filling level indication

The filling level of the waste container can be seen at all times through the inspection window.



www.huer-engel.de/uz174

Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).



*HSM SECURIO B24, B26, B32

www.hsm.eu

