



HSM SECURIO B34 - 1.9 x 15 mm + external autom. oiler

HSM SECURIO B34 document shredder

This premium document shredder in an elegant design provides for data security in an open-plan office. Thanks to the powerful drive, it reliably and quietly shreds the incoming amounts of data of up to eight people.


Technical data

Order number:	18421110	Voltage / Frequency:	230 V / 50 Hz
EAN	4026631031615	Intake width:	310 mm
Cutting type:	particle cut	Container volume / collecting:	100 l
Cutting width:	1,9 mm	Noise level (idle operation):	ca. 56 dB(A)
Particle length:	15 mm	Weight x Depth x Height:	541 x 439 x 845 mm
Security level (DIN 66399):	E-4 F-2 P-5 T-5	Weight:	42 kg
Cutting capacity in sheets 80g/m²:	13 - 15	Shredder material:	Paper, Staples and paper clips, Credit card
Power consumption:	590 W		

Product information



For a consistently high cutting performance, this low maintenance document shredder has an external automatic oiler as an option.



The induction-hardened, solid steel cutting rollers guarantee durability.



Reusable cardboard box as bin for shredded material.



For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



Energy-saving

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



Automatic start/stop

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.



Anti-paper jam function

The paper feed with overload protection reduces paper jams and sustains the high throughput of paper.



Convenient emptying

Robust wooden cabinet with castors. After opening the door, the reusable collecting bag can be easily removed and emptied.



www.huer-engel.de/uz174

Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).

