## **SUPERIOR SERIES INL2159**



## INL2159 - WUXGA - 4000 \*- 16:10 Aspect Ratio

The next generation of Laser Projection is here! With this multi-purpose, multi-use range of laser projectors, you get far more than an image on the wall. Content bursts to life, and viewing becomes an absolute pleasure and a next-level experience in any environment. Viewing presentations in the workplace offers much more crisp detail and readability. Engage more in the classroom and have peace of mind that you and your students or classmates are using the latest cutting-edge, environmentally friendly, energy-efficient display technology on the market.

### **Features**

### **Environmentally-Friendly Laser Technology**

The Superior Series, part of our Quantum Laser line of projectors, are deployed with solid-state laser light source technology. The complete Quantum Laser range is lamp, filter, mercury, and maintenance-free. The ultra-low energy usage for its class and long-standing durability and performance offers outstanding value and low cost of ownership.

### **4K Support**

Simply stunning image quality with up to 1920 x 1200 native resolution and HDMI 2.0 (HDCP 2.2) 4K support. HDR compatible for like life texture details and improved image depth perception.

#### SuperSmartProject

Our SuperSmartProject suite of power-saving, power optimisation, and utiliza-tion features and functions combine ease of use and energy saving for your everyday use. Instant power on, signal power on, instant power off, auto power-off, 10 step illumination reduction, and Dynamic Black optimization all enhance your viewing experience while optimizing energy usage.

#### **Flexible Installation**

Flexibility for almost every surface with front, rear, and ceiling placement as well as floor to ceiling and ceiling to floor projection, full 360-degree placement across the horizontal axis and not forgetting both landscape and portrait modes ideal for retail display purposes, fixed installations, bars, clubs, and restaurants.

#### Image

#### INL2159 - WUXGA - 4000 ♣- 16:10 Aspect Ratio | InFocus.com

Projection Technology	Texas Instruments DLP®
Panel Size	0.48"
Native Resolution	WUXGA
Pixels	1920 x 1200
Aspect Ratio	16:10
Contrast Ratio	300000:1
Brightness (Lumens)	4000
Light Source	Quantum Laser™
Light Source Life Maximum Hours	30000
Maximum Supported Resolution	4096 x 2160
Horizontal Sync. Range (KHz)	15 ~ 100
Vertical Sync. Range (Hz)	23 ~ 120
Uniformity (%)	85

# Optical

Lens	1.3x
Lens Zoom Adjustment	Manual
Optional Lenses	-
Image Offset (%)	110 ±5
Focal Length (mm)	12.81 ~ 16.74
F-Stop	1.94 ~ 2.23
Vertical Lens shift (%)	-
Horizontal Lens shift (%)	-
Keystone Adjustment	Automatic/Manual
Vertical Keystone Correction	±30°
Horizontal Keystone Correction	±30°
Projection Factor	1.21 ~ 1.59:1
Projection Distance (Meters/Feet)	1.0 ~ 7.9 / 3.28 ~ 25.91
Optical Zoom	Manual
Digital Zoom Demagnification / Magnification	0.8x ~ 2.0x
Focus Adjustment	Manual

## Connectivity

Inputs	
Mini D-sub 15-pin (VGA)	
Composite Video	
S-Video	-
HDMI™ 1.4	
HDMI™ 2.0	
USB-B 2.0	-

INL2159 - WUXGA - 4000 *- 16:10 Aspect Ratio   InFocus.com	
RJ45 - LAN 10/100/1000	
3.5 mm Stereo Mini Jack	
3.5 mm Stereo Mini Jack with Microphone	-
Outputs	
Mini D-sub 15-pin (VGA)	-
3.5 mm Stereo Mini Jack	
Powered USB-A for Wireless Dongle	
3D Sync	-
Other	
RS232	
RJ45 HDBaseT	-
All Major 3D Formats	
USB-B 2.0 for Service	-
USB-A for Service	-
Micro USB for Service	
Document Reader	-
Video Player	-
Photo Viewer	-
Music Player	-
12v Screen Trigger	-
Power	
Power Supply	100 ~ 240 V AC; 50 - 60 Hz

211

157

<2

< 0.5

4.6 / 10.1

0 ~ 40 / 32 ~ 104

10000 / 32808

30

10

0~85

-10 ~ 60

0~85

337 x 265 x 119.3 / 13.27 x 10.4 x 4.7

Kensington Lock Port<sup>™</sup>, PIN & Timer Functions

Power Consumption Max (W)

Power Consumption Min. (W)

General

Audio

Security

Fan Noise (dB)

Operating Humidity (%)

Storage Humidity (%)

Power Consumption Standby (W)

Dimensions (W x H x D) (mm / in)

Product Weight (Kilograms/Pounds)

Max Operating Altitude (meters / feet)

Storage Temperature (Celsius/Fahrenheit)

Operating Temperature (Celsius/Fahrenheit)

Power Consumption Network Standby (W)

INL2159 - WUXGA - 4000 \*- 16:10 Aspect Ratio | InFocus.com

,

Copyright © 2022, InFocus and its logo is a registered trademark of InFocus Corporation. Maxnerva Technology Services Limited is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted; all specifications are subject to change without notice. All images are for representation purposes only and may be simulated.