



HYBRID

3-PHASE AIO

ALL-IN-ONE ENERGY STORAGE

Fox storage solutions are available with advanced and intuitive app based remote control and monitoring functionality.



<p>Easy Installation Flexible configuration, plug and play set-up, built-in fuse protection.</p>	<p>High Voltage Includes high-voltage batteries for maximum round-trip efficiency.</p>	<p>IP65 Rated Engineered to last with maximum flexibility. Suitable for outdoor installation.</p>	<p>Remote Monitoring Monitor your system remotely via smartphone app or web portal.</p>
---	---	--	--



UNBALANCED LOADS SUPPORTED
EPS OPTION

BATTERY EXPANSION

EASY UPGRADE



A high-performance, high-efficiency all-in-one system with 10.4kWh of storage capacity.

For more about the Fox range of storage solutions, visit:

WWW.FOX-ESS.COM



TECHNICAL SPECIFICATIONS

Model	AIO-H3-5.0	AIO-H3-6.0	AIO-H3-8.0	AIO-H3-10.0
PV INPUT				
Max. Input Power [W]	A:3000 B:3000	A:4000 B:4000	A:6000 B:4000	A:8000 B:5000
Max. Input Voltage [V]			1000	
Start-up Input Voltage [V]			180	
Rated Input Voltage [V]			720	
MPPT Operating Voltage Range [V]			180-950	
Max. Input Current [A]	14 / 14	14 / 14	26 / 14	26 / 14
Max. Short-circuit Current [A]	16 / 16	16 / 16	32 / 16	32 / 16
No. of Independent MPP Trackers			2	
No. of Strings per MPP Tracker	1 / 1	1 / 1	2 / 1	2 / 1
BATTERY CONNECTION				
BBattery Type			Lithium Battery (LFP)	
Battery Voltage [V]			180-234	
Max. Charge/Discharge Current [A]			26	
Communication Interface			CAN (Communicate with inverter), RS485 (Upgrade BMS)	
AC INPUT AND OUTPUT (GRID)				
Max. AC Input Power [VA]	10000	12000	16000	16000
Max. AC Input Current (per phase) [A]	15.2	18.2	24.2	24.2
Rated Output Power [W]	5000	6000	8000	10000
Max. Output Apparent Power [VA]	5500	6600	8800	11000
Rated Output Current (per phase) [A]	7.2	8.7	11.6	14.5
Max. Output Current [A]	8.8	10.6	14.1	17.6
Rated Grid Voltage [V]		3L/N/PE 380/220; 400/230; 415/240		
Rated Grid Frequency [Hz]		50/60		
Power Factor		1 (Adjustable from 0.8 leading to 0.8 lagging)		
THDi		<3%@Rated Power		
EPS OUTPUT (WITH BATTERY)				
Max. Output Apparent Power [VA]	5000	6000	8000	10000
Peak Output Apparent Power (60s) [VA]	8000	8000	12000	12000
Max. Current (per phase) [A]	7.2	8.7	11.6	14.5
Rated Output Voltage [V]		3L / N / PE 400 / 230		
Rated Output Frequency [Hz]		50/60		
Power Factor		1 (Adjustable from 0.8 leading to 0.8 lagging)		
THDv (linear Load)		<3%@Rated Power		
Switch time [s]		<1.5 (With EPS Box)		
EFFICIENCY				
Euro Efficiency			97.00%	
Max. Efficiency			97.80%	
Max. Battery Charge Efficiency (PV to BAT) (@full load)*			98.50%	
Max. Battery Discharge Efficiency (BAT to AC) (@full load)*			97.00%	
PROTECTION				
Insulation Monitoring			YES	
Residual Current Monitoring			YES	
DC Reverse Polarity Protection			YES	
Anti-islanding Protection			YES	
AC Short-circuit Protection			YES	
AC Overcurrent/Overvoltage Protection			YES	
DC Switch (only for hybrid)			YES	
SPD			DC: Type II, /AC: Type III	
GENERAL DATA				
Dimensions (WxHxD) [mm]			630*1662*389	
Weight [kg]			97 (Except Batteries)	
Installation			Floor-Mounted	
Topology			Transformerless	
Cooling Method			Natural	
Noise Emission [dB]			35	
Max. Operating Altitude [m]			2000	
Operating Temperature Range [°C]			-25 to 60	
Humidity (No Condensation)			0% to 100%	
Protection Degree			IP65	
Standby consumption[W]			< 15	
Monitoring Module			WiFi, LAN, 4G, GPRS (Optional)	
Communication			2*RS485, DRM, Ripple Control, USB	
Display			LCD, App, Website	
STANDARD COMPLIANCE (MORE AVAILABLE UPON REQUEST)				
Safety			EN 62109-1, EN 62109-2, EN 62477-1	
EMC			IEC 61000-6-1, IEC 61000-6-3	
Grid Regulation			EN50549-1, C10/11, VDE-AR-N 4105, G98, CEI 0-21	

* More technical characteristics are available on demand and customized.